

NORTHSTAR™ RANGE FEATURES AND SPECIFICATIONS

	Electric Range	Dual-Fuel Range	All Gas Range
Specifications subject to change without notice.	1954	1955	1956
RANGE WIDTH	30"	30"	30"
RANGE DEPTH (Plus 2" Handle)	28 ½"	28 ½"	28 ½"
Self-Cleaning Electric Oven (4.3 cu. ft.) Oven Size: 25"W x 16"H x 17 1/2"D	•	•	
Self-Cleaning Electric Convection Oven (4.0 cu. ft.) Oven Size: 25"W x 16"H x 16 1/2"D	optional	optional	
Gas Self-Cleaning Oven with Top Broiler (4.0 cu. ft.) Oven Size: 25"W x 15 1/2"H x 17 1/2"D			•
Delayed Start Baking/Cleaning	•	•	•
Variable Temperature Broil	•	•	•
Door-Activated Oven Light with manual over-ride	•	•	•
Heavy Duty, Plated Oven Racks	•	•	•
Porcelain Enamel Broiler Pan	•	•	•
RANGE TOP			
Electric High-Speed Radiant Elements under glass	•		
Gas: Sealed Surface Burners with cast grates		•	•
Converts to L.P. (Propane)		•	•
Electronic Spark with Re-ignition		•	•
Chrome frame around range top	•	•	•
POWER RATINGS			
Power Source (208 to 250V) appliance rating	220V-40A	220V-25A	110V-10A
Radiant Elements, 1,500 watts (Rear Elements)	2		
Radiant Elements, 2,000 watts (Front Left)	1		
Radiant Elements, 2,500 watts (Front Right)	1		
Gas Top Burners, 8,000*BTU NG (Rear Burners)		2	2
Gas Top Burners, 12,000*BTU NG (Front Right)		1	1
Superburner, 15,000*BTU NG (Front Left)		1	1
*Ratings for Liquid Propane approx. 10% lower			
Power Ratings NG (BTUs)		43,000	58,000
Power Ratings LP (BTUs)		38,700	52,200
Power Ratings – Oven burner NG (BTUs)			16,000
Shipping Weight	275 lbs.	285 lbs.	295 lbs.
RANGE OVERALL DIMENSIONS			
30"W x 49"H x 28 ½"D (Plus 2" Handle) – Height to cooking surface is 36".			
All 220V ranges come with standard four wire range cords attached. NOTE: The new electrical standard (Jan. 98) requires that a four wire range cord be used in all new construction. Please advise if a three wire range cord is required (used only in existing construction). Electrical receptacle and gas piping should be installed in approximately the center of opening, 6 inches off the floor.			
STAINLESS STEEL WARMER (Becomes lower storage drawer when warmer option not chosen)			
Located behind the drawer face. Heat settings from proofing (80°) to 225 degrees (F).	optional	optional	not available
Dimensions: 26 ¾ "W x 22 ½ "D x 5 ⅜"H			